






Valve stem packing set - TA 200BR with bull rings

Pre-compressed Packing Set of specially impregnated PTFE fiber packing

Characteristics

Ring set made of pure PTFE packing and PTFE compound bull rings fulfills with a tested leakage rate of 4.2×10^{-5} mbar · l/(s·m) the leakage criteria according to VDI 2440 +200 °C with a maximum allowable leakagerate of 1×10^{-4} mbar l/(sm) at 40 bar.

Operating range

			
p [bar]	25	250	500
v [m/s]	2	0	-
t °C	-200 ... +280		
pH	0 - 14		

Main application



- Valves
- Flaps
- Gate valves
- Fittings

Suitable for

- Power plant technology
- Chemical industry
- Petrochemical plants

Approvals

- TA Luft / VDI 2440 Certificate



All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.

ProPack AG

Rudolf-Diesel-Ring 28 . 82054 Sauerlach

Fon ++49 (0) 8104 6640 0 . Fax ++49 (0) 8104 6640 44

propack@propack.ag

www.propack.ag

TECHNOLOGY MADE IN GERMANY