



S 70 Proglas

Glass Fiber Packing

Characteristics

- No irritation to skin, harmless to health (filament diameter: 6 - 10)
- Non flammable following DIN 4102 – ignition loss <1.5%
- Resistant against oils, grease, steam, solvents and organic acids
- Hydrolytic resistance following DIN 12111: Class 1
- Does not contain toxic substances or heavy metals
- Surface graphite impregnation on request for increasing compactness and nonstick effect
- A variety of products different in form and temperature resistance are available on request

Operating range

t°C	-100 ... +550
pH	3 - 9

Main application

- Furnace, boiler, vessel and chimney doors
- Fireplaces
- Pressureless service closures
- Tunnel furnaces
- Lid seals etc.

Suitable for

- Power plant
- Furnace construction

Variants

- Braided in square or round X-Section
- On request with surface graphite impregnation for increasing compactness and heat conductivity

Form of delivery

Square braided by meter. On request endless rings, frames, special shapes, rectangular or round as well as tadpole tapes.

Square X Section

Standard dimensions / Sales unit

Size	Weight [g/m]	Sales unit [m]
06 x 06	40	200
08 x 08	70	100
10 x 10	100	100
12 x 12	135	50
15 x 15	220	50
20 x 20	400	50
25 x 25	580	25
30 x 30	830	25
40 x 40	1,450	20



All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.

ProPack AG

Rudolf-Diesel-Ring 28 . 82054 Sauerlach

Fon ++49 (0) 8104 6640 0 . Fax ++49 (0) 8104 6640 44
propack@propack.ag

www.propack.ag

TECHNOLOGY MADE IN GERMANY