






P 2P Super

100 % Para-Aramid continuous Fiber with PTFE-Blocking Agent and Silicone free dynamic Run In Lubricant

Characteristics

- Excellent in highly abrasive products
- Wear resistant universal packing
- Minimized monitoring, short run-in period
- Shafts or shaft sleeves in HRC 60 recommended

Operating range

			
p [psi]	360	7250	3630
v [fpm]	4920	300	
t °F	-60 ... +540		
pH	2 - 12		
lb/in ³	0.0452		

Practical useful application data:
max. temperature: +390 °F
max. pressure centrifugal pumps: 290 psi

Main application

- Centrifugal pumps
- Mixer
- Kneader
- Agitators
- Autoclave
- Refiner

Suitable for

- All industries
- Chemical industry
- Waste water technology
- Pulp and paper industry



Form of delivery

This packing can be manufactured from 4 to 40 mm / 3/16" to 1.5" square as well as in intermediate, inch sizes and special measurements.

04-09 mm/3/16"-5/16" on 2 lbs spool
10-15 mm/3/8"-9/16" on 5 lbs spool
16-25 mm/5/8"-1" on 10 lbs spool

Special length, pre-cut or die formed rings on request.

1 lbs of packing of the following cross-sections is equivalent to displayed lengths in feet:

Size	Feet	Size	Feet
4	74.4	13 [1/2"]	7.4
5 [3/16"]	47.6	14 [9/16"]	6.1
6	33.1	15	5.3
6.4 [1/4"]	29.5	16 [5/8"]	4.6
8 [5/16"]	18.6	18	3.7
9.5 [3/8"]	13.2	19 [3/4"]	3.3
10	11.9	20	3.0
11 [7/16"]	9.6	22 [7/8"]	2.5
12	8.3	25 [1"]	1.9

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time. Please note that the technical values cannot be used all at the same time in their maximum values.

ProPack AG

Rudolf-Diesel-Ring 28 · 82054 Sauerlach · Germany

Phone ++49 (0) 8104 6640 0 · Fax ++49 (0) 8104 6640 44
propack@propack.ag

www.propack.ag
TECHNOLOGY MADE IN GERMANY