



Worldwide your competent partner for Sealing Technology



Operating range

	\Diamond	J	I
p [psi]	360	1450	1450
v [fpm]	2360	300	
t°F	-60	+280	
рН	4 - 11		
lb/in ³	0.0488		

Practical useful application data: max. temperature: +250 °F

max. pressure centrifugal pumps: 220 psi

P 8 Ramie

Ramie Fiber with PTFE Blocking Agent and Paraffin Run In Lubricant

Characteristics

- · Universal packing for the lower temperature range
- · Excellent value for money
- Shaft protecting, resistant to rotting
- Recommended shaft surface hardness: HRC 45
- Excellent in products containing solids

Main application

- Centrifugal pumps
- $\cdot \,\, {\rm Gate} \,\, {\rm valves}$
- Fittings
- Agitators
- Refiner
- Filter
- $\cdot\,$ Stern Tube

Suitable for

- Universal use in lower temperature range
- Pulp and paper industry
- Sewage plants
- Marine industries





Form of delivery

This packing can be manufactured from 4 to 40 mm / 3/16" to 1.5" square as well as in intermediate, inch sizes and special measurements.

04-09 mm/3/16"-5/16" on 2 lbs spool 10-15 mm/3/8"-9/16" on 5 lbs spool 16-25 mm/5/8"-1" on 10 lbs spool

Special length, pre-cut or die formed rings on request.

1 lbs of packing of the following cross-sections is equivalent to displayed lenghts in feet:

Size	Feet	Size	Feet
4	68.9	13 [1/2"]	6.8
5 [3/16"]	44.1	14 [9/16"]	5.6
6	30.6	15	4.9
6.4 [1/4"]	27.3	16 [5/8"]	4.3
8 [5/16"]	17.2	18	3.4
9.5 [3/8"]	12.2	19 [3/4"]	3.1
10	11.0	20	2.8
11 [7/16"]	8.9	22 [7/8"]	2.3
12	7.7	25 [1"]	1.8

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time. Please note that the technical values cannot be used all at the same time in their maximum values.

Rudolf-Diesel-Ring 28 . 82054 Sauerlach . Germany Phone ++49 (0) 8104 6640 0 . Fax ++49 (0) 8104 6640 44 propack@propack.ag

ProPack AG

www.propack.ag TECHNOLOGY MADE IN GERMANY