




### A 15

100 % PTFE Tape packing with PTFE yarn cover braid

#### Characteristics

- Low coefficient of friction
- Good adaption to any kind of surface
- Non ageing or hardening
- Used as spiral guarantees simple assembly and disassembly in one piece

#### Operating range

			
p [psi]	290	290	1450
v [fpm]	200	200	
t °F	-330 ... +540		
pH	0 - 14		
lb/in <sup>3</sup>	0.0524		

Practical useful application data:  
max. temperature: +390 °F

#### Main application

- Valve Packing, easy to use

#### Suitable for

- Chemical industry
- Universal use
- Installation and maintenance shops



#### Form of delivery

This packing can be manufactured from 2 mm / 5/64" to 20 mm / 3/4" diameter.

Other lengths and dimensions on request.

All dimensions will be shipped in meters on rolls.

Available meter length for order specifications:

Size	Feet
0.08"	65/164
0.16"	32/164
0.24"	24/164
0.31"	16/98
0.39"	16/98
0.63"	16/65
0.71"	16/65
0.79"	16/65

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.

#### ProPack AG

Rudolf-Diesel-Ring 28 · 82054 Sauerlach · Germany

Phone ++49 (0) 8104 6640 0 · Fax ++49 (0) 8104 6640 44  
propack@propack.ag

[www.propack.ag](http://www.propack.ag)  
TECHNOLOGY MADE IN GERMANY