



## Braided Flange Sealant

Rectangular braided tube packing

### Characteristics

- The elasticity of this gasket tape allows low unevenness of the flange surface
- The sealant can be reused after opening of flange
- Sealing of the cutted ends by inserted point lock



### Main application

- Metal, glass, ceramic flanges on
- boilers
- centrifuges
- pipe flanges
- tanklid
- housings

### Suitable for

- Flanges in General service

### Variant

SL 4, made of ePTFE graphite yarn  
SL 6, made of oiled PTFE yarn  
SL 19, made of PTFE yarn dry  
SL 44 I, made of expanded graphite,  
integrated Inconel reinforcement  
and with adhesive backing



### Form of delivery

15 x 5 mm  
16 x 3 mm  
20 x 4 mm  
22 x 3 mm  
25 x 6 mm  
30 x 4 mm  
33 x 5 mm  
50 x 7 mm

Other dimensions and basic  
materials – on request.



All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.

**ProPack AG**

Rudolf-Diesel-Ring 28 . 82054 Sauerlach

Fon ++49 (0) 8104 6640 0 . Fax ++49 (0) 8104 6640 44  
propack@propack.ag

**www.propack.ag**

**TECHNOLOGY MADE IN GERMANY**