



## S 72 - HT 800

### Glass Fiber Packing

#### Characteristics

- Non flammable
- High electric- and thermal isolation capability
- Dimensionally stabil
- Good mechanical structural strength

#### Operating range

t °F	-150 ... +1,290
pH	3 - 9

Temperature: short term up to +1,500 °F

#### Main application

- Furnace, boiler and chimney doors
- Expansion joints
- Exhaust pipes

#### Suitable for

- Power plant
- Furnace construction

#### Form of delivery

Square braided.  
On request round braided.  
On request with surface graphite  
impregnation for increasing  
compactness and heat conductivity.

#### Square - standard sizes

Standard dimensions / Sales unit

Size	Weight [lb/ft]	Sales unit Feet [ft]
1/4" x 1/4"	0.03	656
5/16" x 5/16"	0.05	328
3/8" x 3/8"	0.07	328
1/2" x 1/2"	0.10	164
9/16" x 9/16"	0.16	164
3/4" x 3/4"	0.27	164
1" x 1"	0.39	82
1 1/4" x 1 1/4"	0.61	82
1 1/2" x 1 1/2"	0.99	66



All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.  
Please note that the technical values cannot be used all at the same time in their maximum values.

**ProPack AG**

Rudolf-Diesel-Ring 28 . 82054 Sauerlach

Fon ++49 (0) 8104 6640 0 . Fax ++49 (0) 8104 6640 44  
propack@propack.ag

[www.propack.ag](http://www.propack.ag)

TECHNOLOGY MADE IN GERMANY