



S 73 - HT 1050

Silicafiber Packing

Characteristics

- Non flammable
- High electric- and thermal isolation capability
- Dimensionally stabil
- Good mechanical structural strength
- Low shrinkage
- Low Volumeloss

Operating range

t °F	-150 ... +1,920
pH	3 - 9

Temperature: short term up to +1,210 °F

Main application

- Furnace, boiler and chimney doors
- Expansion joints
- Exhaust pipes

Suitable for

- Power plant
- Furnace construction

Form of delivery

- Braided in square X-Section
- On request some X-Sections with 0,00039 ft V4A wire reinforcement.

Square - standard sizes

Standard dimensions / Sales unit

Size	Weight [lb/ft]	Sales unit Feet [ft]
5/16" x 5/16"	0.039	328
3/8" x 3/8"	0.064	328
1/2" x 1/2"	0.094	164
9/16" x 9/16"	0.121	164
5/8" x 5/8"	0.134	164
3/4" x 3/4"	0.237	164
1" x 1"	0.363	82
1 1/4" x 1 1/4"	0.524	82



All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.

ProPack AG

Rudolf-Diesel-Ring 28 . 82054 Sauerlach . Germany

Phone ++49 (0) 8104 6640 0 . Fax ++49 (0) 8104 6640 44

propack@propack.ag

www.propack.ag

TECHNOLOGY MADE IN GERMANY