



## P 82

Cotton packing with graphite grease impregnation and Run-In Lubricant

### Characteristics

- Universal packing for the lower temperature range
- Excellent cost-value relation
- Recommended shaft surface hardness: HRC 45
- Smooth braiding for damaged shaft surfaces

### Operating range

p [psi]	150	730	
v [fpm]	1,970	200	
t °F	-4	...	+250
pH	5	-	9
lb/in <sup>3</sup>	0.0542		

### Main application

- Centrifugal pumps
- Agitator

### Suitable for

- Universal use in lower temperature range
- General plant maintenance
- Sewage plants



### Form of delivery

This packing can be manufactured from 6 to 30 mm / 1/4" to 1.2" square as well as in intermediate, inch sizes and special measurements.

- 06-09 mm/1/4"-5/16" on 2 lbs spool
- 10-15 mm/3/8"-9/16" on 5 lbs spool
- 16-25 mm/5/8"-1" on 10 lbs spool

Special length on request.

1 lbs of packing of the following cross-sections is equivalent to displayed lengths in feet:

Size	Feet	Size	Feet
6	27.6	14 [9/16"]	5.1
6.35 [1/4"]	24.6	15	4.4
7	20.2	16 [5/8"]	3.9
8 [5/16"]	15.5	18	3.1
9.5 [3/8"]	11.0	19 [3/4"]	2.7
10	9.9	20	2.5
11 [7/16"]	8.2	22 [7/8"]	2.0
12	6.9	25 [1"]	1.6
12.7 [1/2"]	6.1		

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time. Please note that the technical values cannot be used all at the same time in their maximum values.

ProPack AG

Rudolf-Diesel-Ring 28 . 82054 Sauerlach

Fon ++49 (0) 8104 6640 0 . Fax ++49 (0) 8104 6640 44  
propack@propack.ag

www.propack.ag

TECHNOLOGY MADE IN GERMANY