



### P 84

Para-Aramid Fiber Packing with with graphite grease impregnation and Run-In Lubricant

#### Characteristics

- Wear-resistant universal packing
- Good structural strength
- Recommended shaft surface hardness: HRC 50
- Smooth braiding for damaged shaft surfaces
- Very good price-performance ratio



#### Operating range

p [bar]	15	65	
v [m/s]	10	2	
t °C	-20 ... +150		
pH	2 - 12		
g/cm <sup>3</sup>	1.5		

#### Main application

- Centrifugal pumps
- Mixer

#### Suitable for

- Waste water technology
- Pump industry

#### Variant

- P7 / TP7 with PTFE Blocking Agent and Paraffin Run-In Lubricant
- P7A with PTFE, without lubricant for valves



#### Form of delivery

This packing can be manufactured from 6 to 40 mm square as well as in intermediate, inch sizes and special measurements.

- 06 - 09 mm on 1kg spool
- 10 - 15 mm on 2.5 kg spool
- 16 - 25 mm on 5 kg spool

Special length, pre-cut or die formed rings on request.

1 kg of packing of the following cross-sections is equivalent to displayed meter lengths:

Size mm	Meter	Size mm	Meter
6	18.5	15	3.0
6.35 [1/4"]	16.5	16 [5/8"]	2.6
7	13.6	18	2.1
8 [5/16"]	10.4	19 [3/4"]	1.8
9.5 [3/8"]	7.4	20	1.7
10	6.7	22 [7/8"]	1.4
11 [7/16"]	5.5	25 [1"]	1.1
12	4.6		
12.7 [1/2"]	4.1		
14 [9/16"]	3.4		

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.